

A6510/A7510/A8610

MAIN SPECIFICATIONS

	A6510	A7510	A8610
GENERAL			
Front Interface	HDMI x1, USB C x1, USB A 3.0 x2, USB B 3.0 x1, MIC In x1		
Rear Interface	USB A x3, USB C x1, USB B x3, HDMI In x2, DisplayPort x1, OPS Slot x1, RS232 x1, Audio Out x1, Line out or Headphone x1, SPDIF x1, HDMI Out x1, LAN 1000Base-T x2		
Pre-installed app	Whiteboard, Picture-In-Picture, Eshare, Browser, Settings, Google Play Store, Google Calender, Files by Google, Search, Chrome, Gmail, Maps, YouTube, Drive, YT Music, Google TV, Meet, Photos		
Dimensions: W x D x H (mm)	1,513 x 93 x 953	1,735 x 92 x 1,077	1,981 x 92 x 1,217
Package size: W x D x H (mm)	1,630 x 185 x 1,057	1,859 x 227 x 1,190	2,119 x 225 x 1,320
Weight (kg)	40	52	65
Housing material (face frame/back shell)	Aluminium/metal plate		
Housing colour (face frame/back shell)	Black/black		
VESA	4-M8 screw hole 600 x 400 mm	4-M8 screw hole 800 x 400 mm	4-M8 screw hole 800 x 400 mm
DISPLAY PANEL			
Panel size: diagonal	65" wide	75" wide	86" wide
Effective area: W x H (mm)	1,428 x 803	1,650 x 928	1,895 x 1,065
Resolution: maximum (Full HD)	3,840 x 2,160		
Colours: maximum	1,070,000,000		
Brightness: maximum (cd/m ²)	400		
Contrast ratio	5,000 : 1	5,500 : 1	4,000 : 1
Pixel pitch (mm)	0.124 x 0.372	0.14325 x 0.42975	0.4935 x 0.4935
Response: grey to grey (ms)	6.5	6.5	8
Refreshing frequency	60 Hz		
Viewing angle: H/V (°)	178/178		
LED lifetime	50,000 hours		
TOUCH SYSTEM			
Touch technology	Infrared Touch Frame/Zero Bonding		
Accuracy (mm in touchable area)	1		
Multi touch	Win11/10/8/7/XP, Android		
Single touch	Linux, Mac OS X, Chrome		
Protection glass thickness: including AR coating (mm)	3.2		
Maximum touch points	40		
Coating	Anti-glare, Anti-fingerprint		
Hardness	8 H		
ECOLOGY			
Power consumption: standard mode (W)	< 200		
Power consumption: eco mode (W)	< 133	< 150	< 168
Power consumption: standby mode (W)	< 0.5		
Power consumption: with OPS (W)	< 380	< 420	< 520
Operating temperature (°C)	0 - 40		
Operating humidity (%)	20 - 80		
Altitude limitation: sea level (m)	Lower than 5,000		
Maximum daily operation hours (exclude stand-by time)	Do not use the machine continuously/intermittently for more than 18 hours per day. Failure to do so could result in malfunction.		
Storage temperature	-10°C ~ +50°C		
Storage humidity	15% ~ 80% RH Non-Condensing		
CONTROLLER/ELECTRICAL			
OS	Android 13.0 EDLA		
Audio output power	15 W x2		
RAM	8 GB		
ROM Storage	128 GB		
WIFI	Wif5 Module, Wif6 Module		
Bluetooth	BT 5.2		

A6510/A7510/A8610

MAIN SPECIFICATIONS

A6510

A7510

A8610

ACCESSORIES

Power cable
Touch pen x2
Read this first sheet
Quick guide sheet
Batteries AAAx2
Remote control
USB type C cable (2m)
HDMI 2.0 cable (3m)
USB A-B 3.0 cable (3m)
Plastic clamp(3pcs+3pcs)

For availability of models, options and software, please consult your local supplier.

Ricoh Europe (Netherlands) B.V.

John M. Keynesplein 10-B
1066 EP Amsterdam
The Netherlands



+31 (0)20 5774111



ricoh-europe.com