

M 320 series

M 320
M 320FB
P 310

M2 Office Technology

RICOH
imagine. change.



M 320 series specifications

The M 320 series offers the solution that is right for your needs, whether it's just easy-to-manage and compact printing, or multifunction productivity. Compact footprints make these solutions ideal for smaller spaces and maintenance and management are simple, with intuitive operation.

Features for printers in this series include:

- Crisp 32 pages per minute output
- P 310 is ideal for use on desktops or under counters
- M 320 provides printing, scanning and copying
- M 320FB comes with 4.3 inch touch panel and ARDF
- Best in class security — including SNMPv3-encrypted communications for device monitoring, secure email transmissions by SMTP over SSL/TLS

M 320/ M 320FB/ P 310

MAIN SPECIFICATIONS

	M 320	M 320FB	P 310
GENERAL			
Warm-up time	30 seconds	30 seconds	26 seconds
First output speed: B/W		7.1 seconds	
Continuous output speed		32 ppm	
Memory: standard	256 MB	256 MB	128 MB
Weight	18 kg	18 kg	13 kg
Dimensions: W x D x H	405 x 392 x 407 mm	405 x 392 x 420 mm	370 x 392 x 262 mm
Power source	220 - 240 V, 50 - 60 Hz	220 - 240 V, 50 - 60 Hz	220 - 240 V, 50 - 60 Hz
Laser classification	Class 1 Laser Product (IEC60825 - 1:2014)		
COPIER			
Multiple copying	Up to 99 copies		
Resolution	1,200 x 1,200 dpi		
Zoom	From 25% to 400% in 1% steps		
PRINTER			
Printer language: standard	PCL5e (MAC), PCL6 (Windows & Linux), PostScript3 (Windows)		
Print resolution: maximum	1,200 x 1,200 dpi		
Network interface: standard	Ethernet 10 base-T/100 base-TX, USB2.0 Type B		
Network interface: option	Wireless LAN (IEEE 802.11 a/b/g/n/ac)		
Windows® environments	Windows® 8.1, Windows® 10, Windows® Server 2012, Windows® Server 2012R2, Windows® Server 2016		
Mac OS environments	Macintosh OS X v10.10 or later		
Other supported environments	Linux environment		
SCANNER			
Scanning: B/W	13 ipm	13 ipm	ipm
Scanning: full colour	4.5 ipm	4.5 ipm	ipm
Resolution: maximum	600 dpi	600 dpi	dpi
FAX			
Compatibility	ITU-T (CCITT) G3		
Transmission speed	3 seconds		
Modem speed: maximum	33.6 Kbps		
PAPER HANDLING			
Recommended paper size	Standard paper tray(s): (A4, A5, A6, B5, B6)		
Paper input: standard	300 sheets		
Paper input: maximum	550 sheets		
Paper output: standard	50 sheets	50 sheets	125 sheets
Paper weight	52 - 162 g/m²		
ECOLOGY			
Power consumption: operation	514 W	520 W	512 W
Power consumption: sleep	0.87 W	0.87 W	0.72 W
TEC*	0.42 kWh/week	0.42 kWh/week	0.41 kWh/week
OUTPUT TRAYS AND FINISHER OPTIONS			
1x 250-sheet paper tray			
CONSUMABLES			
Starter toner	1,000 prints		
Toner (regular yield)	3,500 prints		
Toner (high yield)	7,000 prints		
Consumable yield measuring method ISO/IEC 19798			



RICOH
imagine. change.

ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2021 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.