B&W Multifunction Printers

IM 370F IM 460F





Versatile devices for dynamic office environments

The business landscape is constantly changing, and organizations are looking to optimize office space and resources to accommodate hybrid work styles. At the same time, the need for a reliable IT and print infrastructure has grown as businesses seek to seamlessly support digital processes and address security challenges.

This change has created a need for cost-effective and robust workplace technology that streamlines operations, offers the flexibility to easily transition between paper and digital workflows, and provides enhanced data security.

RICOH's latest generation of black-and-white multifunction devices are tailored to support businesses of all sizes in optimizing day-to-day operations with technology that enhances productivity, increases data security, and creates a seamless user experience in a compact all-in-one device.

Experience the versatility of the new IM 370F/IM 460F series — a perfect addition to today's modern workplace that empowers your teams to easily capture, print, share information, and digitize workflows.



Work more efficiently with fast black-and-white print and color scan speeds



Optimize office space with a compact, multifunction device



Protect your business data and intellectual property



Customize options to match your workflow needs with RICOH Smart Integration technology



A comprehensive solution for diverse workflow needs

Enhanced quality, performance, and productivity

Experience the benefits of fast black-and-white print and color scan speeds with our compact letter/legal multifunction device. Enjoy the added convenience of A3 capabilities, allowing you to easily print, copy, and scan A4 pages when needed. What's more, you can personalize and enhance the capabilities of your device with applications and software solutions readily available from the cloud with RICOH Smart Integration.



Improved usability and reliability

Ideal for smaller office workspaces or desktop environments, these latest devices offer space-saving efficiency and low noise levels for uninterrupted focus. RICOH's familiar, user-friendly Smart Operation Panel has been enhanced to provide a more intuitive and seamless user experience with an upgraded OS for better security and usability, as well as improved touch response and faster performance.





Reliable protection of your data

Equipped with the latest controller features, these smart devices provide enhanced privileged account control that gives you more freedom when creating administrator roles. The number of admins has greatly increased, eliminating risks related to sharing IDs. You can also assign different privileges to each role and link it to your user ID system, including Windows and LDAP platforms. Additionally, RICOH's Always Current Technology ensures automatic security and software updates downloaded and installed directly to your device as they become available.



Enhanced sustainability features

As a leader in environmentally-friendly performance, we not only uphold our own commitments but also strive to support your goals. Our new devices utilize almost 17% post-consumer recycled materials for their outer mainframe, while toner bottles are made from 100% recycled plastics. There is zero plastic usage for the toner packaging and the device's optional paper feed unit. The Smart Operation Panel includes new energy-saving features to reduce the operation panel's power consumption by 45% in Sleep Mode.





IM 370F/IM 460F

MAIN SPECIFICATIONS

	50 si 41 374 x 41 220 - 240 ¹ Up to 99 600 From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3TM Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenSc	ver 2012/2012 R2/2016/2019/2022	
First copy speed: B/W First print speed: B/W Continuous output speed Memory: standard Storage: Standard/Optional SPDF capacity Weight Dimensions WxDxH (mm) Power source COPIER Multiple copying Resolution Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	5 seconds 3.8 seconds 37 ppm 6GB (Mainframe 2GB+SOP 4GB) eMMC 56 GB/256 GE 50 si 41 374 x 4¹ 220 - 240 vi Up to 98 600 From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3TM Em Genuine Adobe® PostScript®3TM CP Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-TX/1000 base-TX/1000 base-TX/1001	5 seconds 3.3 seconds 46 ppm 6GB (Mainframe 2GB+SOP 4GB) 8 SSD or 320 GB HDD heets kg 93 x 640 V, 50/60 Hz 99 copies 0 dpi in 1% increments 16270 1.2GHz ullation, PDF Direct Print Emulation , Adobe® PDF Direct Print, IPDS 1 x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B 200 Smart Device Connector Ver 2012/2012 R2/2016/2019/2022	
First print speed: B/W Continuous output speed Memory: standard Storage: Standard/Optional SPDF capacity Weight Dimensions WxDxH (mm) Power source COPIER Multiple copying Resolution Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments UNIX environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	3.8 seconds 37 ppm 6GB (Mainframe 2GB+SOP 4GB) eMMC 56 GB/256 GE 50 si 41 374 x 4' 220 - 240 v Up to 98 600 From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3TM Em Genuine Adobe® PostScript®3TM Em Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenScript®3 Mediands and Script®3 Media	3.3 seconds 46 ppm 6GB (Mainframe 2GB+SOP 4GB) 8 SSD or 320 GB HDD heets kg 93 x 640 V, 50/60 Hz 99 copies 0 dpi in 1% increments 6270 1.2GHz ullation, PDF Direct Print Emulation , Adobe® PDF Direct Print, IPDS 1 x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B 200 Smart Device Connector 2012/2012 R2/2016/2019/2022	
Continuous output speed Memory: standard Storage: Standard/Optional SPDF capacity Weight Dimensions WxDxH (mm) Power source COPIER Multiple copying Resolution Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	37 ppm 6GB (Mainframe 2GB+SOP 4GB) eMMC 56 GB/256 GE 50 si 41 374 x 4* 220 - 240 v Up to 98 600 From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3TM Em Genuine Adobe® PostScript®3TM Em Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenScript®3 Mem	46 ppm 6GB (Mainframe 2GB+SOP 4GB) 8 SSD or 320 GB HDD heets kg 93 x 640 V, 50/60 Hz 99 copies 0 dpi in 1% increments 6270 1.2GHz ullation, PDF Direct Print Emulation , Adobe® PDF Direct Print, IPDS 1 x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B 20th Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
Memory: standard Storage: Standard/Optional SPDF capacity Weight Dimensions WxDxH (mm) Power source COPIER Multiple copying Resolution Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments UNIX environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	6GB (Mainframe 2GB+SOP 4GB) eMMC 56 GB/256 GE 50 si 41 374 x 4 220 - 240 v Up to 98 600 From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3™ Em Genuine Adobe® PostScript®3™ Em Genuine Adobe® PostScript®3™ Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenScript®3 Company (1)	6GB (Mainframe 2GB+SOP 4GB) 3 SSD or 320 GB HDD heets kg 33 x 640 V, 50/60 Hz 99 copies 0 dpi in 1% increments 6270 1.2GHz ullation, PDF Direct Print Emulation , Adobe® PDF Direct Print, IPDS 0 x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B soh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
Storage: Standard/Optional SPDF capacity Weight Dimensions WxDxH (mm) Power source COPIER Multiple copying Resolution Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments UNIX environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	eMMC 56 GB/256 GE 50 si 41 374 x 4' 220 - 240 vi Up to 98 600 From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3TM Em Genuine Adobe® PostScript®3TM Em Genuine Adobe® PostScript®3TM, Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenSc	8 SSD or 320 GB HDD heets kg 93 x 640 V, 50/60 Hz 99 copies 0 dpi in 1% increments 6270 1.2GHz ullation, PDF Direct Print Emulation , Adobe® PDF Direct Print, IPDS 1x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B soh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
SPDF capacity Weight Dimensions WxDxH (mm) Power source COPIER Multiple copying Resolution Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments UNIX environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	50 si 41 374 x 41 220 - 240 ¹ Up to 99 600 From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3TM Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenSc	heets kg 93 x 640 V, 50/60 Hz 19 copies 0 dpi in 1% increments 16270 1.2GHz Iulation, PDF Direct Print Emulation I, Adobe® PDF Direct Print, IPDS Ix 1200 dpi F, USB Host I/F Type A, USB Device I/F Type B Soh Smart Device Connector Iver 2012/2012 R2/2016/2019/2022	
Weight Dimensions WxDxH (mm) Power source COPIER Multiple copying Resolution Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments UNIX environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	41 374 x 4' 220 - 240 ¹ Up to 99 600 From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3TM Em Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-TX/1	kg 93 x 640 V, 50/60 Hz 19 copies 0 dpi in 1% increments 16270 1.2GHz Iulation, PDF Direct Print Emulation I, Adobe® PDF Direct Print, IPDS Ix 1200 dpi F, USB Host I/F Type A, USB Device I/F Type B Soh Smart Device Connector Iver 2012/2012 R2/2016/2019/2022	
Dimensions WxDxH (mm) Power source COPIER Multiple copying Resolution Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments UNIX environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	374 x 4' 220 - 240 ¹ Up to 98 600 From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3™ Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 2	93 x 640 V, 50/60 Hz 99 copies O dpi in 1% increments 6270 1.2GHz ullation, PDF Direct Print Emulation , Adobe® PDF Direct Print, IPDS 1x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B soh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
Power source COPIER Multiple copying Resolution Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments UNIX environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	Up to 95 600 From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3TM Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base- Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenSe	V, 50/60 Hz 19 copies 10 dpi 10 in 1% increments 10 6270 1.2GHz 10 ulation, PDF Direct Print Emulation 10, Adobe® PDF Direct Print, IPDS 10 x 1200 dpi 11, USB Host I/F Type A, USB Device I/F Type B 1200 Smart Device Connector 12 ver 2012/2012 R2/2016/2019/2022	
COPIER Multiple copying Resolution Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments UNIX environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	Up to 95 600 From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3TM Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base- Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenSe	19 copies 10 dpi 10 in 1% increments 10 de 270 1.2GHz 11 control	
Multiple copying Resolution Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments UNIX environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3™ Genuine Adobe® PostScript®3™ Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3	in 1% increments 6270 1.2GHz ullation, PDF Direct Print Emulation , Adobe® PDF Direct Print, IPDS 1x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B soh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
Resolution Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3™ Genuine Adobe® PostScript®3™ Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3	in 1% increments 6270 1.2GHz ullation, PDF Direct Print Emulation , Adobe® PDF Direct Print, IPDS 1x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B soh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
Zoom PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	From 25%-400% Marvell 88PA PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3TM Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-TX/1000 base-TX/1000 base-TX/1001 base-TX	in 1% increments 6270 1.2GHz colored Print Emulation Adobe® PDF Direct Print, IPDS 1x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B coh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
PRINTER CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	Marvell 88PA PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3TM Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenSo	6270 1.2GHz ulation, PDF Direct Print Emulation , Adobe® PDF Direct Print, IPDS 1x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B soh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
CPU Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3™ Up to 1200 Ethernet 10 base-T/100 base-T/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenSe	ulation, PDF Direct Print Emulation , Adobe® PDF Direct Print, IPDS 1 x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B coh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
Printer language: standard Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	PCL5c, PCL6, PostScript®3TM Em Genuine Adobe® PostScript®3™ Up to 1200 Ethernet 10 base-T/100 base-T/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenSe	ulation, PDF Direct Print Emulation , Adobe® PDF Direct Print, IPDS 1 x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B coh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
Printer language: option Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	Genuine Adobe® PostScript®3™ Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenSe	, Adobe® PDF Direct Print, IPDS I x 1200 dpi T, USB Host I/F Type A, USB Device I/F Type B soh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS X UNIX Sun® Solaris, HP-UX, SCO OpenSc	x 1200 dpi r, USB Host I/F Type A, USB Device I/F Type B coh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
Print resolution: maximum Network interface: standard Mobile printing capability Windows® environments Mac OS environments UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	Up to 1200 Ethernet 10 base-T/100 base-TX/1000 base-T Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS X UNIX Sun® Solaris, HP-UX, SCO OpenSc	x 1200 dpi r, USB Host I/F Type A, USB Device I/F Type B coh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
Mobile printing capability Windows® environments Mac OS environments UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	Apple AirPrint™, Mopria, Ric Windows 8.1/10/11; Windows Ser Macintosh OS X UNIX Sun® Solaris, HP-UX, SCO OpenSc	ooh Smart Device Connector ver 2012/2012 R2/2016/2019/2022	
Windows® environments Mac OS environments UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	Windows 8.1/10/11; Windows Ser Macintosh OS X UNIX Sun® Solaris, HP-UX, SCO OpenSo	ver 2012/2012 R2/2016/2019/2022	
Mac OS environments UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	Macintosh OS 3 UNIX Sun® Solaris, HP-UX, SCO OpenSo		
UNIX environments SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	UNIX Sun® Solaris, HP-UX, SCO OpenSe	K v10.15 or later	
SAP® environments Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	·	Macintosh OS X v10.15 or later	
Other supported environments SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard		UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX	
SCANNER Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	SAP® R/3®, SAP® S/4®		
Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	IBM iSeries		
Scanning speed: SPDF Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard			
Resolution: maximum Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	46 ipm (simplex)/92 ipm (duplex)		
Compression method File Formats Scan to FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	Up to 1200dpi		
FAX (Optional) Circuit Transmission speed Modem speed: maximum Resolution: standard	Single Page: TIFF, JPEG, PDF, PDF/A, High Compression PDF, encrypted PDF, Searchable PDF (OCR Option required) Multi Page: TIFF, PDF (Default), PDF/A, High Compression PDF, encrypted PDF, Searchable PDF (OCR Option required)		
Circuit Transmission speed Modem speed: maximum Resolution: standard	Multi Page: TIFF, PDF (Detault), PDF/A, night Compression PDF, encrypted PDF, Searchable PDF (OCR Option required) E-mail, Folder, USB, URL, FTP		
Transmission speed Modem speed: maximum Resolution: standard			
Modem speed: maximum Resolution: standard	PSTN, PBX		
Modem speed: maximum Resolution: standard	3 seconds		
	33.6 Kbps		
Maximum Resolution: option	8x3.85 line/mm, 200x100 dpi		
	16x15.4 line/ mm, 400x400 dpi		
Compression method	MH, MR		
Scanning speed (A4 LEF)	46 spm		
Memory: standard	4 MB, (320 pages)		
Memory: maximum	60 MB, (4,800 pages)		
PAPER HANDLING			
Recommended paper size	Standard Paper Tray: A4 LEF - A6 SEF Bypass Tray: A3 - A6 SEF/Envelope Option Paper Tray: A4 LEF - A6 SEF		
Paper input: standard	500-sheet tray, plus 100-sheet bypass		
Paper input: maximum		2,100 sheets	
Paper output	2.1	250 sheets (A4 or smaller), 100 sheets (larger than A4)	
Paper weight	2,100	100 sheets (larger than A4)	
Paper types	2,100 250 sheets (A4 or smaller), Standard Trays Bypass Tray:	100 sheets (larger than A4) :: 60 - 162 g/m2 52 - 216 g/m2 52 - 162 g/m2	

IM 370F/IM 460F

MAIN SPECIFICATIONS

	IM 370F	IM 460F	
ENVIRONMENTAL FEATURES			
Power consumption: maximum	1,780W		
Power consumption: operation	528.8W	622.5W	
Power consumption: ready mode	26.4W		
Power consumption: sleep mode	0.45W		
TEC	0.38 kWh	0.49 kWh	
CONSUMABLES			
Toner (black)	Standard yield (IM 370F only): 9,000 pages; High-yield (IM 460F only): 15,400 pages		
Waste Toner Bottle	Yield is 50K		
Consumable yields based on 3 pa	iges/job and 6% coverage on A4 paper.		
PAPER SUPPLY OPTIONS			
Paper Feed Unit PB1200 (500-sh	eet tray), Console Type 1647 (cabinet configuration), Console Type 1647 (caster bas	e configuration)	
OTHER OPTIONS			
	Unit Type M54, Fax Connection Unit Type M54*, OCR Unit Type M54, Device Serve XX Memory Unit Type M54 64MB, IEEE 802.11a/b/g/n Interface Unit Type M54, Doc		

^{*} Indicates an item that is non-stocked where extended lead times of up to 5 months is applicable

Some options may not be available at the time of market release.

Specifications and designs are subject to change without notice.

For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.

Some features may require additional options and/or charges.



13 RICOH ricoh.com.au

Ricoh Australia Pty Ltd, Level 1, 2 Richardson Place, North Ryde, NSW 2113, 13 RICOH (13 74 264)

©2023 Ricoh Australia Pty Ltd Ricoh's and the Ricoh Logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners.

©2023 Ricoh Australia Pty Ltd Rich's Reserved. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes not epresentation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them.















